METHOD OF TRANSMITTING DATA IN ACKNOWLEDGED MODE BETWEEN A SENDING UNIT AND A RECEIVING UNIT, AND TRANSMISSION UNIT IMPLEMENTING SUCH A METHOD

5 The present invention relates to techniques for transmitting data in acknowledged mode from a sending unit to a receiving unit.

The invention relates more particularly, among these
10 techniques, to those in which the sending unit, which produces a sequence of blocks each comprising a header plus user data, uses a "polling" mechanism to request acknowledgements of blocks on the part of the receiving unit. The header of each block then comprises an
15 acknowledgement control field activated intermittently by the sending unit so as to request an acknowledgement of blocks on the part of the receiving unit. In response to such a request, the receiving unit returns a message in which a certain number of previous blocks
20 are acknowledged, positively and/or negatively.

A technique of this kind is used, in particular, in third-generation networks.

25 Often, the acknowledgement mechanism is used within the context of an automatic repeat request (ARQ) protocol in which the unit sending the blocks waits for a positive acknowledgement before transmitting the subsequent data. Such a protocol may moreover belong to
30 the class of sliding window protocols so as to acquire a process for control of the stream transmitted. The blocks sent are for this purpose furnished with a sequence number, and the sending unit keeps the list of the sequence numbers of the blocks dispatched but not
35 yet acknowledged as well as that of the sequence numbers of blocks that it may dispatch. The lower bound of the window is shifted when a positive acknowledgement of data sent is received by the sending unit, for example so as to indicate the smallest

sequence number among those of the blocks not yet acknowledged. If an acknowledgement request message has not been correctly received by the receiving unit, the sliding window of the sending unit may remain blocked
5 at an old position, thereby leading to unnecessary repetitions of blocks already received and to significant delays in the transmission of new data.

To reduce the risk of such a blockage of the sliding
10 window, it is possible to increase the level of protection of the blocks transporting the acknowledgement request messages or else, within these blocks, the information transporting the acknowledgement request, so as to decrease the rate of
15 incorrect reception of these requests. Such a method is described in particular in Patent WO 02/069548.

An object of the present invention is to propose an efficient method for transmitting data in packet mode.
20
Another object is to reduce the risks of blockage of the send windows used in certain ARQ mechanisms.

The invention thus proposes a method of transmitting
25 data in acknowledged mode between a sending unit and a receiving unit, in which the sending unit sends the receiving unit a sequence of blocks each comprising a header and data to be transmitted. The header of each block comprises an acknowledgement control field
30 activated intermittently by the sending unit so as to request an acknowledgement of blocks on the part of the receiving unit. According to the invention, the acknowledgement control field for some blocks of the sequence is activated in accordance with a
35 predetermined triggering mode, and the activation of the acknowledgement control field is repeated for at least one block of the sequence that was sent after a block where the acknowledgement control field has been activated in accordance with the predetermined

triggering mode.

The invention can furthermore be implemented according to a method in which the activation of the acknowledgement control field for blocks of the sequence in accordance with the predetermined triggering mode is performed at regular time intervals. It is also possible to repeat the activation of the acknowledgement control field for N consecutive blocks (N being a number at least equal to 1) of the sequence that are sent just after such a block where the acknowledgement control field has been activated in accordance with the predetermined triggering mode, the N blocks moreover possibly being sent to the receiving unit at regular time intervals.

Moreover, the mode of implementation of the invention can provide for the duration over which these N blocks are sent to be substantially shorter than the time intervals between the sendings of blocks where the acknowledgement control field is activated in accordance with the predetermined triggering mode. Thus, the transmission of an acknowledgement request is protected by a mechanism for repeating this request a limited number of times. The duration over which the repetitions are sent can be tailored in such a way as not to occupy the bandwidth of the system for too long a time with messages for supervising the link.

In one embodiment of the invention, a particular processing of the blocks received having the control field activated is applied by the receiving unit so as to avoid the dispatching of redundant acknowledgement information.

In a first embodiment, the receiving unit is instructed such that after having received a first block of the sequence having the acknowledgement control field activated, it takes no account of the possible

activation of the acknowledgement control field for another block of the sequence that was received in a period of predetermined duration after the first block.

5   Another possibility consists in the receiving unit being instructed such that after having returned acknowledgement information in response to the receipt of a first block of the sequence having the acknowledgement control field activated, it prohibits
10   the dispatching of acknowledgement information in a period of predetermined duration after the first block of the sequence.

Advantageously, provision may moreover be made for this
15   predetermined duration to correspond substantially to N times a time interval separating the sendings of two consecutive blocks of the sequence when one chooses to repeat the activation of the acknowledgement control field for N consecutive blocks (N > 1) of the sequence
20   that were sent just after a block where the acknowledgement control field has been activated in accordance with the predetermined triggering mode.

The present invention has moreover as subject a unit
25   for transmitting data in acknowledged mode, comprising means for producing at least one sequence of blocks each comprising data to be transmitted and a header including an acknowledgement control field, means for sending the blocks of the sequence to a receiving unit,
30   and means of intermittent activation of the acknowledgement control field in the header of the blocks of the sequence so as to request an acknowledgement of blocks on the part of the receiving unit. The means of intermittent activation comprise
35   first means for activating the acknowledgement control field for some blocks of the sequence in accordance with a predetermined triggering mode, and second means for repeating the activation of the acknowledgement control field for at least one block of the sequence

that was sent after a block where the acknowledgement
control field has been activated by the first means.

The said first means may furthermore be arranged so as
5   to activate at regular time intervals the
acknowledgement control field for blocks of the
sequence. The second means may also advantageously be
devised so as to activate the acknowledgement control
field of N consecutive blocks of the sequence that were
10 sent just after the block where the acknowledgement
control field has been activated by the first means, N
being a number at least equal to 1, the N blocks
possibly being sent to the receiving unit at regular
time intervals when N > 1. In the latter case,
15 provision may be made for the duration for which the
said N blocks are sent to be substantially shorter than
the time intervals between the sendings of blocks where
the acknowledgement control field is activated by the
first means.
20

Other features and advantages of the present invention
will become apparent in the description below of
nonlimiting exemplary embodiments, with reference to
the appended drawings, in which:
25

-   Figure 1 is a diagram of a UMTS network to which
the invention may be applied;
-   Figure 2 is a chart showing the organization as
layers of communication protocols employed on the radio
30 interface of the UMTS network;
-   Figure 3 is a chart of exchanges of protocol units
illustrating an implementation of the invention;
-   Figure 4 is a chart of exchanges of protocol units
illustrating an implementation of the invention;
35 -   Figure 5 is a diagram of a data transmission unit
according to the invention.

The invention is described below in its application to
a UMTS network operating in FDD (frequency division

duplex) mode. Figure 1 shows the architecture of such a UMTS network.

The switches of the mobile service 10, belonging to a
5 core network (CN), are linked on the one hand to one or more fixed networks 11 and on the other hand, by means of a so-called *lu* interface, to command equipment 12 or RNCs ("Radio Network Controllers"). Each RNC 12 is linked to one or more base stations 13 by means of a
10 so-called *lub* interface. The base stations 13, distributed over the territory covered by the network, are capable of communicating by radio with the mobile terminals 14, 14a, 14b called UE ("UMTS Equipment"). The base stations can be grouped together to form nodes
15 called "node B". Certain RNCs 12 may furthermore communicate with one another by means of a so-called *lur* interface. The RNCs and the base stations form an access network called UTRAN ("UMTS Terrestrial Radio Access Network").
20

The UTRAN comprises elements of layers 1 and 2 of the ISO model with a view to providing the links required on the radio interface (called Uu), and a stage 15A for controlling the radio resources (RRC, "Radio Resource
25 Control") belonging to layer 3, as is described in the 3G TS 25.301 technical specification "Radio Interface Protocol Architecture", version 3.9.0 published in December 2001 by the 3GPP (3rd Generation Partnership Project). In view of the higher layers, the UTRAN acts
30 simply as a relay between the UE and the CN.

Figure 2 shows the RRC stages 15A, 15B and the stages of the lower layers which belong to the UTRAN and to a UE. On each side, layer 2 is subdivided into a radio
35 link control (RLC) stage 16A, 16B and a medium access control (MAC) stage 17A, 17B. Layer 1 comprises a coding and multiplexing stage 18A, 18B. A radio stage 19A, 19B caters for the transmission of the radio signals from trains of symbols provided by the stage

.18A, 18B, and the reception of the signals in the other direction.

There are various ways of adapting the architecture of
protocols according to figure 2 to the hardware
architecture of the UTRAN according to figure 1, and in
general various organizations can be adopted depending
on the types of channels (see section 11.2 of the
3G TS 25.401 technical specification "UTRAN Overall
Description", version 3.1.0 published in January 2000
by the 3GPP). The RRC, RLC and MAC stages are typically
located in the RNC 12. When several RNCs are involved,
the MAC sublayer can be apportioned among these RNCs,
with appropriate protocols for the exchanges on the lur
interface, for example ATM ("Asynchronous Transfer
Mode") and AAL2 ("ATM Adaptation Layer No. 2"). These
same protocols may also be employed on the *lub*
interface for the exchanges between the MAC sublayer
and layer 1.

Layers 1 and 2 are each controlled by the RRC sublayer,
whose characteristics are described in the 3G TS 25.331
technical specification "RRC Protocol Specification",
version 3.1.0 published in October 1999 by the 3GPP.
The RRC stage 15A, 15B supervises the radio interface.
Moreover, it processes streams to be transmitted to the
remote station according to a "control plan", as
opposed to the "user plan" which corresponds to the
processing of the user data arising from layer 3.

The RLC sublayer is described in the 3G TS 25.322
technical specification "RLC Protocol Specification",
version 3.9.0 published in December 2001 by the 3GPP.
In the send direction, the RLC stage 16A, 16B receives,
according to the respective logical channels, data
streams consisting of service data units (RLC-SDU)
arising from layer 3. An RLC module of the stage
16A, 16B is associated with each logical channel so as
in particular to perform a segmentation of the RLC-SDU

units of the stream into blocks, or protocol data units
(PDU, "Packet Data Units") addressed to the MAC
sublayer and comprising an RLC header. In the receive
direction, an RLC module conversely performs a
reassembling of the RLC-SDU units of the logical
channel from the blocks received from the MAC sublayer.

According to the logical channels and under the control
of the RRC stage, the RLC sublayer can render a
transfer service in transparent mode, in acknowledged
mode or in nonacknowledged mode. An acknowledgement
mechanism based on sequence numbers of the blocks sent
is provided for in acknowledged mode. Two types of
protocol unit blocks of the RLC sublayer are
distinguished: the information transfer blocks ("data
PDUs") and, for the acknowledged mode only, the control
blocks ("control PDUs"). Among the latter, the "STATUS"
control block allows in particular the receiving entity
to indicate to the sending entity the information
transfer blocks that have been correctly received and
those that have been lost during transmission.

The receiving entity in fact sends on request or
spontaneously supervision reports ("status reports") to
the sending unit that consist of one or more "STATUS"
control blocks. An acknowledgement control function
makes it possible to instruct the triggering of the
activation of an acknowledgement request according to
one or more predetermined modes. The standard currently
makes provision for several activation modes, each
being defined by a particular triggering condition. The
triggering condition may for example consist of the
expiry of a supervision report requests periodicity
timer ("Timer_Poll_Periodic"), in such a way as to
trigger the periodic dispatching to the receiving unit
of a report request.

Each acknowledged-mode information transfer block ("AMD
PDU") comprises a header field and a field of data to

be transmitted. The header of each block comprises an acknowledgement control field, consisting of a bit termed the polling bit, which may be activated to request a report of reception of blocks on the part of the RLC sublayer of the receiving unit. The request is thus sent by setting this polling bit to 1.

The MAC sublayer is described in the 3G TS 25.321 technical specification "MAC Protocol Specification", version 3.1.0 published in October 1999 by the 3GPP. It transposes one or more logical channels onto one or more transport channels TrCH. In the send direction, the MAC stage 17A, 17B can multiplex one or more logical channels in one and the same transport channel. On such a transport channel, the MAC stage 17A, 17B delivers successive transport blocks TrBk each consisting of an optional MAC header and an RLC-PDU unit arising from an associated logical channel.

For each TrCH, the RRC sublayer provides the MAC sublayer with a set of transport formats (TFS, "Transport Format Set"). A transport format comprises a transmission time interval TTI equal to 10, 20, 40 or 80 ms, a transport block size, a transport block set size and parameters defining the protection scheme to be applied in the TrCH by layer 1 for detecting and correcting transmission errors. Depending on the current bit rate on the logical channel or channels associated with the TrCH, the MAC stage 17A, 17B selects a transport format from the TFS assigned by the RRC sublayer, and it delivers in each TTI a set of transport blocks complying with the selected format, whilst indicating this format to layer 1.

The acknowledged-mode information transfer blocks AMD PDU are numbered by an integer sequence number, denoted SN ("Sequence Number"). The RLC entity of the sending unit keeps an updated set of state variables, including:

- an acknowledged state variable VT(A) that indicates the sequence number which immediately follows the sequence number of the last acknowledged AMD PDU block. The variable VT(A) thus points to the current
5 lower bound of a send window. The updating thereof is performed on receipt of an acknowledgement;
- a send window size state variable VT(WS) ("Transmission Window state variable");
- a send state variable VT(MS) ("Maximum Send state
10 variable"), the value of which represents the upper bound of the send window and is determined according to the relation VT(MS) = VT(A) + VT(WS).

The send window makes it possible to control the
15 sending of blocks of a sequence whose previous blocks have not yet been acknowledged by the receiving unit. In most cases, the RLC send entity will prohibit itself from transmitting blocks whose sequence number exceeds the current value VT(MS). The acknowledged state
20 variable being updated on receipt of the acknowledgement of a block of specified sequence number, the loss of one or more supervision report requests may lead to the blockage of the send window, even though the corresponding data have been correctly
25 received by the receiving unit without it being possible for their acknowledgement to be sent in the absence of a supervision report request.

According to a preferred mode of embodiment of the
30 invention, it is proposed that at least one repeat of the report request generated in response to the realization of a condition of triggering of the acknowledgement control function be transmitted to the receiving unit in addition to this request. These
35 request repeats, when they are multiple, are transmitted at a substantially higher tempo than that of the requests generated in response to the realization of a condition of triggering of the acknowledgement control function. In a UMTS system, the

transmission of the multiple repeats is preferably
performed at regular intervals, typically corresponding
to a TTI interval. The transmission of the request
repeats on successive blocks within one and the same
5   TTI interval would in fact probably limit the
efficiency thereof. The simple presence of fading on
the transmission channel would give rise not only to
the loss of the block transporting the request, but
also that of the succeeding blocks and hence of the
10 request repeats.

Figure 3 illustrates a mechanism according to the
invention between the RLC entities of a sending unit 30
and of a receiving unit 31. The sending unit may be
that of an RNC controller in the case of UMTS, and the
15 receiving unit that of a UE. The time axis relating to
the sending unit 30 is divided according to an
interval, regular in the example illustrated, which may
correspond to a TTI transmission interval. The
condition of triggering of the acknowledgement control
20 function of the sending unit 30 is configured in such a
way that the triggering of the function takes place at
an instant $T_{i+1} = T_i + M \times TTI$ spaced $M \times TTI$ from the
previous triggering that occurred at the instant T_i. At
the instant T_i a supervision report request is
25 therefore sent to the receiving unit (AMD PDU block
i,0, bit P of which is set to 1). Figure 3 illustrates
the case where this request is not received by the
receiving unit, and does not therefore give rise to the
30 dispatching of a supervision report by the receiving
unit. According to the invention, N (in the example,
N = 2 < M) repeats of the request of the block AMD PDU
i,0 (blocks AMD PDU, i,1 and i,N) are sent, so as to
alleviate the possible loss of the block AMD PDU i,0,
35 or of the N-1 blocks AMD PDU i,1...N-1. These repeats
are sent at the tempo of one per TTI interval. Blocks
AMD PDU, i,N+1 to AMD PDU i,M-1 sent at the instants
$T_i + (N+1) \times TTI$ to $T_i + (M-1) \times TTI$ have for their part a
polling bit set to zero (P = 0). Figure 3 thus

illustrates the sending of AMD PDU blocks i,j at each
TTI interval, the index i corresponding to the time
interval between the instants T_i and $Ti + (M-1) \times TTI$
during which M blocks are sent, and the index j
5   illustrating the values taken by a counter of these M
blocks reset to zero with each block sent following the
triggering of the acknowledgement control function.

At the instant T_{i+1}, the triggering of the
10   acknowledgement control function occurs thereby
generating the dispatching of a new request to the
receiving unit (AMD PDU block i+1,0). This request is
also repeated N times (the polling bit of the AMD PDU
blocks i+1,1...N is set to 1).
15

Figure 3 illustrates moreover the fact that M is
preferably chosen in such a way as to be substantially
greater than N. The choice of the ratio N/M results
from a compromise aimed at effectively limiting the
20   risk of window blockage while avoiding the dispatching
of too large a quantity of repeats.

Figure 4 illustrates a further mode of embodiment of
the invention, in which the use of a report prohibit
25   timer makes it possible to prevent the dispatching of a
supervision report for each of the request repeats. The
report prohibit timer ("Timer_Status_Prohibit") makes
it possible to prohibit the dispatching of one or more
consecutive supervision reports by the receiving unit.
30   This timer is set upon the dispatching of the
supervision report responding to the first request
received by the receiving unit, whether this be the
request triggered by the acknowledgement control
function or one of the N repeats of this request.
35   Preferably, this timer is set with a value equal to or
greater than $N \times TTI$ so as to cover the maximum
duration for which request repeats are liable to be
received by the receiving unit. A single supervision
report (STATUS PDU, i,2) is generated on the expiry of

the timer, however many requests are received while it is running. In this way, a first supervision report (STATUS PDU i,1) is dispatched in response to the receipt of the first request received, then a second report (STATUS PDU i,2) is dispatched on expiry of the prohibit timer. The possible loss of one of these two reports may thus advantageously be compensated for.

A timer making it possible to completely ignore the requests received could equally well be used, without thereby modifying the nature of the present invention. Just as before, this timer would advantageously be set with a value equal to or greater than N × TTI upon the dispatching of the supervision report responding to the first request received by the receiving unit, whether this be the request triggered by the acknowledgement control function or one of the N repeats of this request.

Figure 5 illustrates certain means of the sending unit (40) according to the invention. These means pertain to the instance of the acknowledged-mode RLC protocol created at the RNC (case of a downlink) or at the UE (case of an uplink) to support the transfer of the AMD PDU blocks.

The sending unit comprises a module (41) for managing report requests (polling) which will control the setting of the polling bit within the AMD PDU blocks produced by the production module (45) with a view to being sent by the module (42) to the RLC protocol instance created at the level of the receiving unit (47). The module (41) comprises a first module (44) for activating the polling bit upon triggering, for example periodic according to the Timer_Poll_Periodic parameter, of the acknowledgement control function ("polling trigger").

Send parameters for the request repeats are held in a

second module (43) for activating the polling bit so as to repeat acknowledgement requests. These parameters comprise, for example, the number N of repeats and their pace (1 repeat per TTI interval). They can be

5 communicated to the RLC protocol instance by the RRC layer, by means of an RRC control module (46) which configures the module (43).

The aforesaid parameters could also advantageously be

10 held in a database of for example MIB type ("Management Information Base" — see in particular RFC recommendation 2737 of the Internet Engineering Task Force, published in December 1999), and be updated by way of an operation and maintenance system (O&M).

15

The modules (43) and (44) will drive a module (48) for activating the polling bit in the header of the blocks sent. This module (48) indicates the value of the polling bit to the module (45). It activates the

20 polling bit (P = 1) for each repetition in accordance with the parameters held in the module (43), and according to each activation requested by the module (44).

25 For the implementation of the method illustrated in Figure 4, the transmission unit comprises, in one embodiment of the invention, means (46) for activating the use of the report prohibit timer ("Timer_Status_Prohibit") by the receiving unit (47).

30 The procedures of the RRC protocol comprise procedures for managing radio resources described in Section 8.2 of the aforesaid technical specification 3G TS 25.331. The configuration of this timer is thus driven by the RRC layer (module 46), by means of configuration

35 messages ("RADIO BEARER SETUP" or "RADIO BEARER RECONFIGURATION" messages) which make it possible to transmit this timer's setting value to the receiving unit ("RLC Info" and "Downlink RLC Status Info" information units described in paragraphs 8.6.4.9,

10.3.4.23 and 10.3.4.1, respectively).

In an alternative embodiment of the invention, the control module (46) for the RRC layer instructs the
5   receiving unit such that it takes no account of supervision report requests received over a predetermined duration following the dispatching of the report responding to a first request received.

10   The triggering of the acknowledgement control function is instructed by the RRC layer, by way of the "CRLC-Config-Req" primitive, described in paragraphs 8.1 and 8.2 of the aforesaid 3G TS 25.322 specification, as well as in paragraph 5.1.1 of the aforesaid
15   3G TS 25.301 technical specification. In particular, the value of the periodic triggering timer "Timer_Poll_Periodic" may if appropriate be defined in this way, as illustrated in Figure 5.

20   The TS 25.322 technical specification allows the sending of AMD PDU blocks that do not contain data to be transmitted. The data field of such blocks contains padding bits. The module (45) produces AMD PDU blocks from the supervision information to be transmitted
25   (including the information for activating if appropriate the polling bit) and from data to be transmitted. In situations where there is no longer any data to be transmitted, but where the module (43) instructs the dispatching of an acknowledgement request
30   repeat, the module (45) can admittedly generate an AMD PDU block whose polling bit is set to 1 and which contains no data to be transmitted. It can however advantageously also generate an AMD PDU block whose polling bit is set to 1 and whose data field reproduces
35   that of the last AMD PDU block sent containing data to be transmitted (preferably not having already been acknowledged), or else simply ignore the polling bit activation instructed by the module (43).